

|                          |                        |  |
|--------------------------|------------------------|--|
| <b>Aluminium Base</b>    | Alloy                  | 6063T6   |
|                          | Finish                 | Bright Anodised AA5  |
|                          |                        | Satin Silver Anodised AA5  |
| <b>Dimensions</b>        | Width                  | 60mm   |
|                          | Depth                  | 14mm   |
|                          | Length                 | 2000mm (standard base)   |
|                          | Weight                 | 0.665 kg/mt  |
| <b>Activation Insert</b> | Materials:             | Flexible PVC-DVF406  |
|                          | Dimensions (external)  | Standard length rolls - 5, 10, 15mt  |
|                          | Max Width              | 54mm   |
|                          | Max depth              | 9mm  |
|                          | Active impact zone     | 34mm   |
|                          | Weight/mt (inc Copper) | 0.353kg/mt   |
|                          | Colours                | Red- 033HMF/25K-200. Green<br>-GN590HMF/25K-200.Blue<br>-BE047HMF/25K-200. |
|                          | Elongation @ break (%) | 380  |
|                          | Shore A15 Hardness     | 63   |
|                          | UV stabilised          | yes  |
|                          | Cold Flex Temp         | -28 c  |
|                          | Tensile (Mpa)          | 14   |
|                          | I.P. Rating            | IP65   |
| <b>Contact Conductor</b> | Material               | ED Copper  |
|                          | Width                  | 10mm   |
|                          | Quality                | CTS790   |
|                          | Treatments             | Zinc-Chromate Passivated   |
| <b>LED Light Strip</b>   | Dimensions             | 8mm x 2.5mm  |
|                          | LEDs/mt                | 30   |
|                          | Colour                 | Bright White   |
|                          | Operating Temperature  | -25c to +60c   |
|                          | Voltage                | DC 12v   |
|                          | LED Life               | 50,000 hours   |
|                          | Power consumption      | <a href="#">180mA/metre@12V (see note1)</a>                                |
| <b>LED Controller</b>    | Supply Voltage         | 12V DC   |
|                          | Supply Current         | 80mA + LED current (see note 1)  |
| <b>End Caps</b>          | Construction           | 2 part - self locking  |
|                          | Material               | ABS  |
|                          | Weight (set)           | 42 grams   |

**Crona**   
safe-zone

**Crona**   
safe-zone

*Note 1: LED Current dependent on control setting choice - Max 180mA/metre full brightness.*

*Current is reduced by changing choice of light mode*

**For more information call our sales team on 01943  
876600**

**or email: [sales@cronapress.co.uk](mailto:sales@cronapress.co.uk)**

|                                  |   |                       |
|----------------------------------|---|-----------------------|
| <b>Optional Extras</b>           |   |                       |
| <b>Finishes</b>                  | Any coloured anodised finish to special order | Minimum order applies |
| <b>Anti-Microbial Protection</b> | Product                                       | Hygienilac            |
|                                  | Standards                                     | BS6250 sever usage    |
|                                  | Approvals                                     | FDA, HSE, EPA, NHS    |